

EXTANT CLAIMS

Following are clean copies of the extant claims, including any further amendment requested herewith:

1. (PREVIOUSLY AMENDED) A method for clipping graphics primitives for display, comprising the steps of:
performing a clipping algorithm which uses only a single circular buffer to store input and output vertices of a primitive; and
5 for each one of said vertices, indicating whether said one of said vertices is visible with respect to each plane of a view volume.
2. The method of Claim 1, wherein only vertices which are visible in all said planes are rasterized.
3. (PREVIOUSLY AMENDED) The method of Claim 1, wherein said performing step is executed prior to any lighting, fog, or texture calculations.
7. The method of Claim 1, wherein said view volume is a frustrum.
8. The method of Claim 1, wherein there are six or more planes in said view volume.
9. The method of Claim 1, wherein there are six planes in said view volume.
10. The method of Claim 1, wherein there are twelve planes in said view volume.
11. The method of Claim 1, wherein said clipping algorithm is the Sutherland and Hodgman polygon clipping algorithm.

12. The method of Claim 1, wherein vertex visibility in each of said planes is indicated by a bit flag.
13. The method of Claim 1, wherein vertex visibility is indicated by twelve bit code.
15. The method of Claim 1, wherein said circular buffer has a maximum storage of sixteen vertices.
16. (PREVIOUSLY TWICE AMENDED) A geometry unit, comprising:
circuitry to define all vertices of a primitive using relational coordinates;
circuitry to implement a clipping algorithm which uses only a single
5 circular buffer to store input and output vertices of a primitive;
and
circuitry to set an outcode value for each of said vertices indicating whether it is visible with respect to individual planes of said view volume.
17. The geometry unit of Claim 16, wherein only vertices which are visible in all said planes are rasterized.
18. The geometry unit of Claim 16, wherein said clipping algorithm is implemented prior to any lighting, fog, or texture calculations.
19. (PREVIOUSLY AMENDED) The geometry unit of Claim 16, wherein said outcode value indicates whether said vertex is visible with respect to each plane of said view volume.
20. The geometry unit of Claim 16, wherein said primitive is a triangle.

21. The geometry unit of Claim 16, wherein said relational coordinates are barycentric.
22. The geometry unit of Claim 16, wherein said view volume is a frustrum.
23. The geometry unit of Claim 16, wherein there are six or more planes in said view volume.
24. The geometry unit of Claim 16, wherein said clipping algorithm is the Sutherland and Hodgman polygon clipping algorithm.
25. The geometry unit of Claim 16, wherein vertex visibility in each of said planes is indicated by a bit flag.
26. The geometry unit of Claim 16, wherein two circular buffers are used to store said input and output polygons.
27. The geometry unit of Claim 16, wherein said circular buffer has a maximum storage of sixteen vertices.
29. (PREVIOUSLY AMENDED) The pipelined graphics system of Claim 36, wherein only vertices which are visible in all said planes are rasterized.
30. (PREVIOUSLY AMENDED) The pipelined graphics system of Claim 36, wherein said clipping is implemented prior to any lighting, fog, or texture calculations.
31. (PREVIOUSLY AMENDED) The pipelined graphics system of Claim 36, wherein said primitive is a triangle.

32. (PREVIOUSLY AMENDED) The pipelined graphics system of Claim 36, wherein said view volume is a frustrum.
33. (PREVIOUSLY AMENDED) The pipelined graphics system of Claim 36, wherein there are six or more planes in said view volume.
34. (PREVIOUSLY AMENDED) The pipelined graphics system of Claim 36, wherein said clipping uses the Sutherland and Hodgman polygon clipping algorithm.
35. (PREVIOUSLY AMENDED) The pipelined graphics system of Claim 36, wherein vertex visibility in each of said planes is indicated by a bit flag.
47. The method of Claim 1, further comprising defining all said vertices of said primitive using relational coordinates.

48. A computer system comprising:
- display hardware;
 - a processor connected to provide graphics data;
 - a geometry and lighting accelerator connected to receive said graphics data, said geometry and lighting accelerator comprising
 - a transformation unit connected to transform a primitive into a clipping space, and
 - a geometry unit connected to
 - perform clip testing on said primitives,
 - clip said primitives, if necessary,
 - set an outcode value for each said vertex indicating whether it is visible with respect to each plane of a view volume, and
 - output clipped graphics data to be rendered; and
 - video rendering hardware connected to receive said clipped graphics data and to generate graphics, and connected to display said graphics on said display hardware;
- wherein said geometry unit uses only a single circular buffer to store input and output vertices of said primitive.
49. The computer system of Claim 48, wherein said clipping is implemented prior to any lighting, fog, or texture calculations.
50. The computer system of Claim 48, wherein said primitive is a triangle.
51. The computer system of Claim 48, wherein said clipping uses the Sutherland and Hodgman polygon clipping algorithm.
52. The computer system of Claim 48, wherein vertex visibility in each of said planes is indicated by a bit flag.